

PVC Conduit - Schedule 40

Wheatland Tube schedule 40 PVC, which is manufactured in compliance with UL651 and ASTM 1784 specifications, sets the standard for durability and reliability in both underground and above ground applications. Designed to withstand the harshest conditions, our rigid nonmetallic PVC conduit is built to resist corrosive forces and ensure that the conduit maintains its structural integrity over time, even when exposed to moisture, sunlight, chemicals, or other corrosive elements.

- UL 651 file #E530286
- NEMA TC2
- Sunlight resistant per UL651
- Manufactured with one integral solvent-weld bell standard per length
- UL Listed for max 90°C conductors
- Corrosion resistant
- 10' and 20' Lengths



Part Number	Size	Average OD	Minimum Average ID	Minimum Wall Thickness	Bell Depth	Weight Per Foot	Bundle Quantity	Weight Per Bundle
		in	in	in	in	lbs	ft	lbs
P40-050	½"	0.840	0.578	0.109	1.50	0.165	6,000	990
P40-075	¾"	1.050	0.780	0.113	1.75	0.220	4,400	968
P40-100	1"	1.315	1.004	0.133	2.00	0.326	3,600	1,174
P40-125	1¼"	1.660	1.335	0.140	2.25	0.441	3,300	1,455
P40-150	1½"	1.900	1.564	0.145	2.75	0.528	2,250	1,188
P40-200	2"	2.375	2.021	0.154	3.00	0.730	1,400	1,022
P40-250	2½"	2.875	2.414	0.203	3.25	1.158	930	1,077
P40-300	3"	3.500	3.008	0.216	3.75	1.609	880	1,416
P40-350	3½"	4.000	3.486	0.226	4.00	1.935	630	1,219
P40-400	4"	4.500	3.961	0.237	4.50	2.292	570	1,306

PVC Conduit - Schedule 80

Wheatland Tube schedule 80 PVC, which is manufactured in compliance with UL651 and ASTM 1784 specifications, sets the standard for durability and reliability in both underground and above ground applications. Designed to withstand the harshest conditions, our rigid nonmetallic PVC conduit is built to resist corrosive forces and ensure that the conduit maintains its structural integrity over time, even when exposed to moisture, sunlight, chemicals, or other corrosive elements.

- UL 651 file #E530286
- NEMA TC2
- Sunlight resistant per UL651
- Manufactured with one integral solvent-weld bell standard per length
- UL Listed for max 90°C conductors
- Corrosion resistant
- 10' and 20' Lengths



Part Number	Size	Average OD	Minimum Average ID	Minimum Wall Thickness	Bell Depth	Weight Per Foot	Bundle Quantity	Weight Per Bundle
		in	in	in	in	lbs	ft	lbs
P80-050	½"	0.840	0.502	0.147	1.500	0.205	6,000	1,230
P80-075	¾"	1.050	0.608	0.154	1.750	0.278	4,400	1,223
P80-100	1"	1.315	0.910	0.179	2.000	0.410	3,600	1,476
P80-125	1¼"	1.660	1.227	0.191	2.250	0.565	3,300	1,865
P80-150	1½"	1.900	1.446	0.200	2.750	0.728	2,250	1,638
P80-200	2"	2.375	1.881	0.218	3.000	1.004	1,400	1,406
P80-250	2½"	2.875	2.250	0.276	3.250	1.531	930	1,424
P80-300	3"	3.500	2.820	0.300	3.750	2.049	880	1,803
P80-350	3½"	4.000	3.820	0.318	4.000	2.499	630	1,575
P80-400	4"	4.500	3.737	0.337	4.500	3.122	570	1,780